

GRAPHICS - PROMOTIONAL

Issue date : 27/10/2008
Date last modification : 30/08/2022

4-GL3B-12755 UK and Ireland Bus Vinyl

Face Material

Gloss white soft vinyl, with a repositionable adhesive system developed specifically for short to medium term vehicle signage. e.g. bus side advertising campaigns. Ideal for silk screen printing.

Type	Soft vinyl	
Colour and Finish	Gloss white	
Weight	140 g/m ² ±10%	ISO-536
Thickness	100 µ ±10%	ISO 534-80

Adhesive

Repositionable adhesive with good adhesion to Correx.

Reference	RI - AVM
Type	Acrylic semi-permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C / +100°C
Shear	High
Tack	Medium N/inch ²
Final Adhesion	Medium N/inch

Liner

Type	1 side clay coated	
Colour and Finish	White	
Weight	140 g/m ² ±10%	PP-032 - ISO 536
Thickness	135 µ ±10%	ISO 534

Applications

For short to medium term vehicle signage, eg bus side advertising campaigns. Good adhesion to Correx. Not recommended for direct contact to painted surfaces or glass

Printing Methods

Solvent based and UV screen printing, offset UV. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

