

## DATA SHEET

### H996 DOUBLE COATED FOAM TAPE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC (SOLVENT BASED)
LOOP TACK	FINAT-9 4.0KG/25MM (CARRIER BROKEN)
LINER	3MIL GREEN POLYOLEFIN
CARRIER	4 PCF PE FOAM
PEEL ADHESION	PSTC-3 1.85KGS/25MM (CARRIER BROKEN)
SHEAR STRENGTH	OVER 24 HOURS WITH 1KG SANDWICH LOADING ON 2 STAINLESS STEEL PLATES 25MM X 25MM AT 25°C
HEAT RESISTANCE	OVER 24 HOURS WITH 0.5KG SANDWICH LOADING ON 2 STAINLESS STEEL PLATES 25MM X 25MM AT 80°C
NORMAL TENSILE STRENGTH	OVER 20KG/25MM X 25MM
THICKNESS	1.0MM $\pm$ 0.1MM
SERVICE TEMPERATURE	-20 TO 90°C
COLOUR	BLACK

#### PRODUCT FEATURES AND APPLICATIONS

HIGH TACK PERMANENT ADHESIVE WITH EXCELLENT AGING AND WEATHER RESISTANT PROPERTIES  
SPECIFICALLY DESIGNED FOR MOUNTING AND JOINING NAMEPLATES, PLASTIC TRIM, SIGNS, EMBLEMS AND DECORATIVE TRIM

THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND THE USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

DATE OF ISSUE : JUNE 2021

[WWW.ADMIRALPSP.CO.UK](http://WWW.ADMIRALPSP.CO.UK)