














DirectTex[®] Softimage Contrast[®]

Fields of application

.01 .02 .03 .04 .07

Specifications

	REF. 599150 150
	100 % polyester knit fabrics PVC-free, recyclable
	ca. 160/ 252/ 320/ 505 cm ca. 63/ 99/ 126/ 199 inch other widths available on request
	B-s1, d0 DIN EN 13501-1
	ca. 210 g/m ² ca. 6.2 oz/yd ²
	ca. 0.37 mm ca. 370 µm
	rolls 50/ 100 m 55/ 109 yd
	length: 448.7 N cross: 683.6 N DIN EN ISO 13934-1
	length: 31.4 % cross: 53.3 % DIN EN ISO 13934-1
	blank: 7 DIN EN ISO 105-B02
	blank: 88.76 DIN 5033-1
	length: 0.9 % cross: 0.7 % DIN EN 14704-1
	cold, ultrasonic cut

Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside			

Article shrinkage (33 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,5 %	1,2 %	185
190°C	/ %	/ %	
200°C	/ %	/ %	
210°C	/ %	/ %	

Certifications



DirectTex® Softimage Contrast

Fields of application

.01 .02 .03 .04 .07



Preview print sample