

DirectTex[®]

Softimage Creaseless Premium[®]

Fields of application

.02 .04 .05 .07

Specifications



599221 159



100 % polyester
knit fabrics
PVC-free, recyclable



ca. 160/ 252/ 320/ 505 cm
ca. 63/ 99/ 126/ 199 inch
other widths available on request



B-s1, d0 DIN EN 13501-1
M1 NF P 92 503-507
NFPA 701



ca. 220 g/m²
ca. 6.5 oz/yd²



ca. 0.41 mm
ca. 410 μm



rolls
50/ 100 m
55/ 109 yd



length: 438.7 N
cross: 1477.4 N
DIN EN ISO 13934-1



length: 50.7 %
cross: 50.6 %
DIN EN ISO 13934-1



blank: 7
DIN EN ISO 105-B02



length: 1.5 %
cross: 0.5 %
DIN EN 14704-1



cold, ultrasonic cut

Printing methods

| print | UV | Latex | Dyesub |
|---------|----|-------|--------|
| Inside | • | • | • |
| Outside | | | • |

Article shrinkage (50 sec hold up time)

| | shrinkage in cross direction | shrinkage in longitudinal direction | recommended fixing temperature |
|-------|---------------------------------|--|-----------------------------------|
| 180°C | 1,5 % | 0,8 % | |
| 190°C | 1,7 % | 0,9 % | • |
| 200°C | 2,2 % | 1,0 % | |
| 210°C | 3,5 % | 1,2 % | |

Certifications



DirectTex® Softimage Creaseless Premium

Fields of application

.02 .04 .05 .07



Ref.-Nr.: 599221 159 | Preview print sample