

# DirectTex® Flag Supreme

Fields of application

**.02 .04 .05 .06 .07**

## Specifications



599096 141



100 % polyester  
knit fabrics  
PVC-free, recyclable



ca. 160/ 252/ 320/ 505 cm  
ca. 63/ 99/ 126/ 199 inch  
other widths available on request



B-s1, d0    DIN EN 13501-1



ca. 90 g/m<sup>2</sup>  
ca. 2.65 oz/yd<sup>2</sup>



ca. 0.28 mm  
ca. 280 µm



rolls  
100 m  
109 yd



blank:    55.8 %  
DIN EN 410



length:    395.8 N (15.4 N)  
cross:    425.2 N (15.3 N)  
DIN EN ISO 13934-1 (13934-2)



length:    23.5 %  
cross:    64.2 %  
DIN EN ISO 13934-1



length:    0.7 %  
cross:    12.4 %  
DIN EN 14704-1



cold, heat, ultrasonic cut



UV stable

## Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside			

## Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,4 %	1,2 %	•
190°C	0,5 %	1,2 %	
200°C	0,6 %	1,2 %	
210°C	0,7 %	1,5 %	

## Certifications



## DirectTex® Flag Supreme

Fields of application

**.02 .04 .05 .06 .07**



Preview print sample