

POLI-FIX 326

Product Information

Universally applicable double-sided adhesive tape with an excellent initial tack.

The synthetic rubber offers a limited resistance against temperature and plasticisers.

POLI-FIX 326 guarantees an adhesion on unpolar surfaces such as polyethylene and polypropylene.

Especially to be emphasised are the following properties:

- Mounting of foam, felt and fabric.
- Mounting of displays, product samples, paper, carton and synthetic materials.

Technical Data

Carrier:	Fleece	
Adhesive:	Synthetic rubber	
Liner:	Silicone-paper, yellow (95 g/m ²)	
Adhesion [N/cm]:	8,50	+/- 10 %
Thickness [mm]:	0,10	+/- 5 %
Temperature resistance [°C]:	-20 / +70	

Standard Dimensions

1.500 mm x 100 m

1.500 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH Zeppelinstraße 17 53424 Remagen – GERMANY

Phone: +49 (0) 2642 - 9836 0 Fax: +49 (0) 2642 - 9836 37

E-Mail: info@poli-tape.de Internet: www.poli-tape.de 28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.