

Floor & Wall-R Product Information

General

Floor & Wall-R is a 150 micron textured white PVC laminated with a removable clear acrylic adhesive. The product is for short to medium term indoor applications. The product is suitable for printing by Latex, UV & most solvent based inks.

Product is suitable for

- Short to Mid Term Application
- Indoor Use
- POS Signage/ General Signage
- Wall Graphics
- Floor Graphics – Applicable to
 - concrete/stone floor
 - wooden/laminated floors
 - carpets (low pile carpets –but should be tested on small area to prove performance)
 – **Not suitable for use on some types of PVC flooring, ceramic tiles and natural stone***

Product Benefits are

- Product removes cleanly, with minimal residue transfer to surface
- For ease of application Floor & Wall R is supplied with an ‘air free’ structured release liner
- Slip Resistant
- Fire Resistant
- No lamination required
- Good scratch resistance

Standard Sizes

Width: 1370mm
 Length: 50m

Product Features and Performance Data

Face Material	Textured White Monomeric PVC	150 µm ± 10
Adhesive	Acrylic water based PSA moderate tack	26 µm ± 2
Liner	Structured air release, 1 side siliconized	135 µm ± 10
Application temperature		10C to 40C
Slip Test	DIN 51130: 2014	R10
Fire Test	EN13501-1:2007 +A1 2009	C-s1 d0

This information is given as a guideline and due to the wide variation in surface to which this product may be applied the end user MUST carry out suitable testing to satisfy themselves as to satisfactory performance. Due to the wide variation in potential surfaces Print Solutions cannot accept any responsibility for the adhesive performance in the event of adhesion failure.