

CHARACTERISTICS		
PVC FACE FILM	Type	Calendered Monomeric soft PVC film
	Thickness	80 ± 10µm
	Color Code	White
	Shrinkage	≤ 0.8%
	Surface Tension	≥ 30dn/cm
	Opacity	> 80%
Adhesive	Type	Clear solvent based permanent pressure sensitive glue
	Weight (g/m ²)	18 ± 2
	Adhesion Temperature	15°C ~ 40°C
	180° Peeling Force	≥ 10N/25mm 20min GB2792-81
	Initial Adhesion-Ball Track	≥ 5# Steel Ball GB4852-84
	Holding Power	≥ 1440min GB4854-84
Liner	Type	Double side polycoated kraft paper
	Color	White
	Weight	120g ± 5g/m ²
	Release Force	0.05 ~ 0.2 N/25mm
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics application.	
Compatibility of printers and ink	Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki, Roland, Vutek and HP Scitex. Inks should be the original ink from the printers manufacturers. The best printing temperature is 35-40°C .	

Published information concerning bsmart products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.

Because of the variety of uses of bsmart products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages.

All specifications are subject to change without prior notice.