



A POLI-TAPE GROUP Company

TEC LUX 600 Gloss

Product Information

Polyester film (transparent gloss, 23 μ) with an ultra clear solvent based acrylic adhesive (permanent), laminated on a one-sided claycoated silicone paper liner (90 g/m²).

Particularly suitable for protection of digital prints and images to avoid influence of UV, dirt and humidity.

The perfect transparency of the film and the adhesive ensure colour enhancement and the best image brightness.

TEC LUX 600 Gloss improves outdoor print duration and reduces fading and damage of the prints due to weather conditions.

Due to the good resistance of the polyester film to solvents, it can be successfully used as „anti-graffiti“ film when proper felt pens are used.

Particularly suitable for application on flat, curved and slightly corrugated surfaces.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Recommendations for laminating

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

Technical Data

Carrier:	clear polyester film
Thickness:	23 μ +/- 5 %
Adhesive:	ultra clear solvent acrylic, permanent
Adhesion:	7,5 N/cm
Liner:	one-sided clay-coated silicone paper (90 g/m ²)
Application temperature:	+10 - +40 °C
Temperature durability :	- 40 - +80 °C
Outdoor durability:	> 2 years

Standard Dimensions

1370 mm x 50 m
1050 mm x 50 m
1550 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501

Fax: +39 0481 882 440

E-Mail: info@kemicasrl.it

Internet: www.kemica.it

06/09/2016

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.