

CHARACTERISTICS		
PVC FACE FILM	Type	Calendered Monomeric soft PVC film
	Thickness	160 ± 10um
	Color Code	Ceramic white
	Back	Black
	Shrinkage	≤ 0.6%
	Opacity	> 99%
	Holes No.	Average 130/sq in
	Hole Diameter	1.62mm
	Distance between Holes	Left-Right 1.25mm Up-Down 2.0mm
	Hole Space	40%
Adhesive	Type	Clear solvent based removable pressure sensitive glue
	Weight (g/m ²)	30 ± 5
	Adhesion Temperature	15°C ~ 40°C
	180° Peeling Force	5N /25mm FTM1
	Initial Tack - Loop Track	≥ 2N/25MM*25MM (FTM9)
	Holding Power	≥ 1440min (FTM8)
Liner	Type	Laminated Kraft paper (additional liner)
	Color	White
	Weight	186g ± 10g/m ²
	Release Force	0.05 ~ 0.25 N/25mm
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	Suitable for vehicle graphics and window graphics	
Compatibility of printers and ink	Media is suitable for all solvent and eco solvent digital printers including Mimaki, Roland, Vutek and HP Scitex. Also for UV printing. Inks should be the original ink from the printer manufacturers. The best printing temperature is 35-40°C .	

Published information concerning bsmart products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.

Because of the variety of uses of bsmart products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages.

All specifications are subject to change without prior notice.