






for digital and screen printing

Product Range			
Range (th./weight)	2,4mm-450gr and 2,6mm-600gr	3mm-900gr; 5mm-1600gr; 8mm-2000gr; 10mm-3000gr	From 2,4 mm to 5 mm From 450 gr to 1600gr
Applications	Digital and Screen Printing - Transformation – Economic Material for indoor signage corona treated, suitable for printing in large numbers	Digital and film adhesive application - Material for indoor and outdoor signage with corona treatment, UV and FR	Total opacity, no light through Two sides printing RAL color core on demand Patent pending



Corona treatment



UV Protection



Flame retardant

Product Range	2.4 mm PRINTOLYTE® Bubble Guard Matt Plus + ®	2.6 mm PRINTOLYTE® Bubble Guard Matt Plus + ®	3 mm BGMATT® Bubble Guard Matt Plus + ®	5 mm BGMATT® Bubble Guard Matt Plus + ®	8 mm BGMATT®	10 mm BGMATT®
Weight (gr/sqm)	450	600	900	1600	2000	3000
Formats (mm Standard)	1220x2440 1530x3050 2050x3050 Others on demand					
Colour	WHITE The other Colours/RAL on demand					
Treatment	Corona Treatment (44/42 dynes) – UV protection					
Special Treatment	Flame retardant (on demand)					



CORONA treated and approved by main manufacturers of flat bed printers..

HP Latex technology /
DURST / MIMAKI / EFI Futek /
Onset / SwissQprint

MaterialSolutions

Western Industrial Estate
Naas Road, Dublin 12
Ph: +353 1 409 8000 | sales@materialsolutions.ie